



Material Safety Data Sheet

FIR No.: 048396
Version Number: US-US-2

Level: 3
Release Date: 2005-08-02

1. Product and Company Identification

Product Name: SAE 75W-140 Synthetic Rear Axle Lubricant
Product Code: See Attachment
Application: Rear axle lubricant
Supplier: Ford Motor Company
 Attention: MSDS Information, P.O. Box 1899
 Dearborn, Michigan 48121
 1-800-392-3673

Emergency Telephone: Poison Control Center: 1-800-959-3673
 CHEMTREC: U.S. and Canada: 1-800-424-9300
 CHEMTREC: International: 1-703-527-3887

2. Composition/Information on Ingredients

This chemical product is a preparation.

Chemical Name	CAS Number	Percent Concentration	Hazard Classification
PETROLEUM DISTILLATES HYDROTREATED HEAVY PARAFFINIC	64742-54-7	1-5	HAZCOM

3. Hazards Identification

Health: This product has low volatility and so is not expected to cause respiratory tract irritation during normal conditions of use. Exposure to high mist levels in poorly ventilated areas may cause temporary irritation to the upper respiratory tract. No skin irritation can be expected from single short-term exposure to this product. Prolonged or repeated contact may produce some irritation.

Physical and Chemical Hazards: This product is combustible at high temperatures.

Environment: Material contains a chemical which is a Hazardous Air Pollutant (HAP), regulated by the United States Clean Air Act.

4. First-Aid Measures

Inhalation: If gas/fume/vapor/dust/mist from the material is inhaled, remove the affected person immediately to fresh air.

Skin Contact: Wash skin with soap and water. If irritation persists, get medical attention.

Eye Contact: In case of contact with eyes, rinse immediately with plenty of water for at least 15 minutes and seek medical attention. If irritation persists, get medical attention.



Material Safety Data Sheet

FIR No.: 048396
Version Number: US-US-2

Level: 3
Release Date: 2005-08-02

Ingestion: If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.

Notes to a Physician: There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-Fighting Measures

Extinguishing Media: EXTINGUISHER INFORMATION: Dry chemical, foam, carbon dioxide.

Specific Methods: Use water to cool fire-exposed containers, structures, and to protect personnel.

Specific Hazards: Irritating and/or toxic fumes and gases may be emitted upon heating of this product.

6. Accidental Release Measures

Personal Precautions: Ventilate the contaminated area.
Wear appropriate protective equipment and clothing during clean-up.

Environmental Precautions: Do not allow this material to drain into sewers/water supplies.

Methods for Cleaning Up: Attempt to reclaim the free product, if this is possible.

7. Handling and Storage

Handling:

Technical Measures: No special precautions necessary.

Precautions and Advice for Safe Handling: Use with adequate ventilation.

Storage:

Technical Measures: No special precautions.

Storage Conditions: Keep the container tightly closed and in a cool, well-ventilated place. Storage temperatures should not exceed 40 C.

8. Exposure Controls/Personal Protection

Control Parameters: If oil mist is generated, observe the OSHA exposure limit of 5 mg/m3. Ford Motor Company recommends an exposure limit of 1.0 mg/m3.



Material Safety Data Sheet

FIR No.: 048396
Version Number: US-US-2

Level: 3
Release Date: 2005-08-02

Personal Protective Equipment:

Respiratory Protection: None required under normal conditions.
Hand Protection: The use of nitrile-latex gloves is recommended.
Eye Protection: Wear safety glasses.
Skin and Body Protection: Use of protective coveralls and long sleeves is recommended. Wash thoroughly after handling.
Hygiene Measures: Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Specific Gravity: 0.87 15.6 Deg C
Physical State: LIQUID
Odor: MILD BLAND
Color: LIGHT COLORED
pH: N.AV
Temperature Range During which Changes in Physical State Occur:
Boiling Point: N.AV
Freezing Point: N.AV
Flash Point: +150 °C COC
Auto-ignition Temperature: +354 °C
Explosion Properties:
UEL: N.AV
LEL: N.AV
Vapor Pressure: N.AV
Vapor Density: N.AV
Solubility: INSOLUBLE
Viscosity: 185@40C CST
Evaporation Rate: N.AV



LINCOLN



Mercury

Motorcraft

Rotunda

Material Safety Data Sheet

FIR No.: 048396
Version Number: US-US-2

Level: 3
Release Date: 2005-08-02

10. Stability and Reactivity

Stability: Stable at ambient and moderately elevated temperatures and pressures.
Hazardous polymerization will not occur.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other low molecular weight hydrocarbons.
Decomposition of this product may emit hydrogen sulfide.
Decomposition of this product may emit oxides of sulfur.

11. Toxicological Information

103-24-2 DI-2-ETHYL HEXYL AZELATE
Oral, adult rat, LD50 = 8720 mg/kg
103-24-2 DI-2-ETHYL HEXYL AZELATE
Skin, adult rabbit, LD50 = 20 gm/kg

Inhalation: Inhalation of vapors (generated at high temperatures only) may cause mild irritation of the nose, throat, and respiratory tract.

Skin Contact: Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.
Prolonged or repeated contact with this product may dry and/or defat the skin.

12. Ecological Information

Ecotoxicity: The acute EC50 for freshwater fish is 100 - 1000 ppm based on component data.

13. Disposal Considerations

Waste from Residues: Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulation.

Contaminated Packaging: No consideration given when disposed of according to local, state, and Federal regulations.



Material Safety Data Sheet

FIR No.: 048396
Version Number: US-US-2

Level: 3
Release Date: 2005-08-02

14. Transport Information

U.S. Department of Transportation (DOT) 49 - CFR 172.101

This product is not regulated as a dangerous good.

Canadian Transportation of Dangerous Goods (T.D.G.) - TDGR Schedule II

This product is not regulated as a dangerous good.

Secretary of Communication and Transportation (SCT) - NOM-002-SCT2/1994 (Mexico)

This product is not regulated as a dangerous good.

International and Domestic Air Transportation - ICAO & IATA Section 4.2

This product is not regulated as a dangerous good.

International Water Transportation - IMDG Code Amendment 31-02

This product is not regulated as a dangerous good.

15. Regulatory Information

The components of this product are listed on the TSCA Inventory

WARNING: This product and the product being replaced may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Material contains a chemical which is a Ford Motor Company Material of Concern. Use and release of this material should be minimized to the greatest extent possible.

16. Other Information



Key/Legend: N.AP = Not applicable; N.AV = not available; ND = Not determined or No data; TLV = Threshold limit value; TWA = Time-weighted average; STEL = Short-term exposure limit; C = Ceiling limit

Preparation Information:

The chemical identification and properties for this material were provided by the manufacturer. For Canadian locations, a manufacturer's MSDS is available upon request. Health and safety information has been evaluated by the Occupational and Environmental Health Sciences Department, Ford Motor Company, National Parts General Office, MD74, 29500 Plymouth Road, Livonia, MI 48150, USA.

Disclaimer:

The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.



Material Safety Data Sheet

FIR No.: 048396
Version Number: US-US-2

Level: 3
Release Date: 2005-08-02

Attachment

Product Code	Container Size	Part of Kit	Kit Product Code
XY-75W140-QL	1 qt		
XY-75W140-QL1	1 qt		