

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 26BR HIGH TEMP RTV RED SILICONE GASKET MAKER 3 OZ
Item No: 81160
Product Type: Silicone

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredients | Percent | ACGIH 8 Hr. TWA: | OSHA 8 Hr. TWA: |
|-------------------------------------|---------|--------------------------------------|---------------------------------------|
| POLYDIMETHYLSILOXANE 63148-62-9 | 80-90 | Not Listed | Not Listed |
| AMORPHOUS SILICA 7631-86-9 | 5-15 | 10 mg/m ³ TWA | 6 mg/m ³ TWA |
| METHYLTRIAACETOXSILANE 4253-34-3 | 1-10 | Not Listed | Not Listed |
| ETHYLTRIAACETOXSILANE 17689-77-9 | 1-10 | Not Listed | Not Listed |
| IRON OXIDE 1309-37-1 | 1-10 | 5 mg/m ³ (Fe) | 10 mg/m ³ (Fe) particulate |
| ACETIC ACID 64-19-7 | **** | 10 ppm TWA; 25 mg/m ³ TWA | 10 ppm TWA; 25 mg/m ³ TWA |

3. HAZARDS IDENTIFICATION

Toxicity: ****When this product is exposed to moisture, 1-3% acetic acid may be formed. May cause eye and skin irritation. May irritate lips, gums, tongue, mouth, nose and throat. May be harmful if swallowed. When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde. Oral LD50 = 2060 mg/kg. Note: This product does not contain microcrystalline silica.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.

Signs and Symptoms of Exposure: Acetic acid produced during curing irritates eyes, nose and throat. Repeated skin contact may cause allergic skin reactions.

| Ingredients | Percent | NTP: | ACGIH Carcinogens | IARC: |
|-------------------------|---------|------|-----------------------|---------|
| IRON OXIDE 1309-37-1 | 1-10 | | A4 - Not Classifiable | Group 3 |

Medical Conditions Recognized as Being Aggravated by Exposure: Methyltriacetoxysilane: Eye, skin and pulmonary disorders.

4. FIRST AID MEASURES

Ingestion: Rinse mouth. If swallowed, seek medical advice immediately and show this container or label.

Inhalation: Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wipe off paste with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): More than 200 degrees F. Method: Tag Closed Cup

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products Formed by Fire or Thermal Decomposition: Acetic acid, Formaldehyde, Silica fume,

Unusual Fire/Explosion Hazards: None

Lower Explosive Limit:
Upper Explosive Limit:

Acetic acid: 4%
Acetic acid: 19.9% @ 200 degrees F.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Store in a dry area below 90 degrees F. Keep container closed when not in use.
Handling: Avoid contact with skin and eyes. Do not inhale vapors.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Rubber or plastic gloves
Ventilation: Provide adequate ventilation
Respiratory Protection: not required under normal use In case of insufficient ventilation, wear suitable respiratory equipment

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Red paste
Odor: Acetic acid
Boiling Point (°F): Not applicable, polymeric material
pH: Does not apply
Solubility in Water: Polymerized
Specific Gravity: 1.03
VOC Content(Wt.%): 4.8% by weight; 0.42 lb/gal; 50.48 g/l
Vapor Pressure: 10 mm Hg @ 80 degrees F.
Vapor Density (Air=1): Not Determined
Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur
Incompatibilities: Polymerized by contact with moisture. Acetic acid liberated.
Conditions to Avoid: Exposure to moisture
Hazardous Products Formed by Fire or Thermal Decomposition: Acetic acid, Formaldehyde, Silica fume,

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: NONE
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: not regulated
Class or Division: None

Product name: 26BR HIGH TEMP RTV RED SILICONE
GASKET MAKER 3 OZ

Item 81160

UN/NA Number: None

IMDG

Proper Shipping: Unrestricted

Hazard Class: None

UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA
06106

Revision Date: 01/30/2004

Revision 4

Number:

Telephone Number: 1-87-Permatex (877) 376-2839