



MATERIAL SAFETY DATA SHEET

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label) Full Throttle Engine Treatment (FTE 50)	DATE 3-16-06
MANUFACTURER'S NAME QMI	EMERGENCY TELEPHONE #: QMI: (800) 255-8138 CHEM-TEL: (800) 255-3924
ADDRESS (Number, Street, City, State and Zip Code) 3606 Craftsman Blvd., Lakeland, FL 33803 USA	
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO. None	
ADDITIONAL HAZARD CLASSES (as applicable) In accordance with OSHA 29 CFR 1910-1200.	
CHEMICAL FAMILY Petroleum	FORMULA Proprietary

SECTION II (list ingredients)

CAS REGISTRY NO.	%W	%V	CHEMICAL NAME(S)	LISTED AS A CARCINOGEN
64742-54-7	85		Distillates Hydrotreated Heavy Paraffinic	Not Listed
64742-65-0			Distillates Solvent Dewaxed Heavy Paraffinic	Not Listed
Proprietary	>2		Non-Toxic Surfactant	Not Listed
9002-84-0	>1		P.T.F.E.	Not Listed

SECTION III - PHYSICAL DATA

BOILING POINT N.D.A.	SPECIFIC GRAVITY 0.89	
VAPOR DENSITY (AIR=1) N/A	EVAPORATION RATE N/A	PERCENT SOLID BY WEIGHT (%) 2%
SOLUBILITY IN WATER Insoluble		
APPEARANCE AND ODOR Dark Amber Liquid, Mild Odor		IS MATERIAL: <u>LIQUID</u> SOLID GAS PASTE POWDER

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT 428°F 220°C	METHOD USED COC	FLAMMABLE LIMITS	LEL N/A	UEL N/A
EXTINGUISHING MEDIA Carbon Dioxide Foam and Dry Chemical and Water Fog				
SPECIAL FIRE FIGHTING PROCEDURES Water spray may be used to keep exposed containers cool, (enclosed fires) self-contained breathing apparatus must be used.				
UNUSUAL FIRE AND EXPLOSION HAZARDS None				

